

# ***HANKONG***



TRUCK & BUS RADIAL TIRES

QINGDAO HANKONG TYRE LTD.

297 Fenghuangshan Road, West Coast New Area, Qingdao, China.

Tel: +86-532-83978005

Email: [sales@hankongtyre.com](mailto:sales@hankongtyre.com)

<https://www.hankongtyre.com>







## HKS1

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5     | 14PR       | 144        | 142  | M            | 8.25        | 7.50,8.25      | 2800         | 2650 | 720           | 720  | 1054            | 279               | 15              |
| 11R22.5     | 16PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 830           | 830  | 1054            | 279               | 15              |
| 11R24.5     | 14PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 720           | 720  | 1104            | 279               | 15              |
| 11R24.5     | 16PR       | 149        | 146  | M            | 8.25        | 7.50,8.25      | 3250         | 3000 | 830           | 830  | 1104            | 279               | 15              |
| 295/75R22.5 | 14PR       | 144        | 141  | M            | 9.00        | 8.25,9.00      | 2800         | 2575 | 760           | 760  | 1014            | 298               | 15              |
| 295/75R22.5 | 16PR       | 146        | 143  | M            | 9.00        | 8.25,9.00      | 3000         | 2725 | 830           | 830  | 1014            | 298               | 15              |
| 285/75R24.5 | 14PR       | 144        | 141  | M            | 8.25        | 8.25           | 2800         | 2575 | 760           | 760  | 1050            | 283               | 15              |
| 285/75R24.5 | 16PR       | 147        | 144  | M            | 8.25        | 8.25           | 3075         | 2800 | 830           | 830  | 1050            | 283               | 15              |
| 12R22.5     | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 16              |



## HKD30

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5     | 14PR       | 144        | 142  | L            | 8.25        | 7.50,8.25      | 2800         | 2650 | 720           | 720  | 1065            | 279               | 23              |
| 11R22.5     | 16PR       | 146        | 143  | L            | 8.25        | 7.50,8.25      | 3000         | 2725 | 830           | 830  | 1065            | 279               | 23              |
| 295/75R22.5 | 14PR       | 144        | 141  | L            | 9.00        | 8.25,9.00      | 2800         | 2575 | 760           | 760  | 1020            | 298               | 23              |
| 295/75R22.5 | 16PR       | 146        | 143  | L            | 9.00        | 8.25,9.00      | 3000         | 2725 | 830           | 830  | 1020            | 298               | 23              |
| 11R24.5     | 14PR       | 146        | 143  | L            | 8.25        | 7.50,8.25      | 3000         | 2725 | 720           | 720  | 1116            | 279               | 23              |
| 11R24.5     | 16PR       | 149        | 146  | L            | 8.25        | 7.50,8.25      | 3250         | 3000 | 830           | 830  | 1116            | 279               | 23              |
| 285/75R24.5 | 14PR       | 144        | 141  | L            | 8.25        | 8.25           | 2800         | 2575 | 760           | 760  | 1056            | 283               | 23              |
| 285/75R24.5 | 16PR       | 147        | 144  | L            | 8.25        | 8.25           | 3075         | 2800 | 830           | 830  | 1056            | 283               | 23              |



## HKD50


| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5     | 16PR       | 150        | 147  | M            | 9.00        | 8.25,9.00      | 3350         | 3075 | 830           | 830  | 1085            | 300               | 21              |
| 12R22.5     | 18PR       | 152        | 149  | L            | 9.00        | 8.25           | 3550         | 3250 | 930           | 930  | 1085            | 300               | 21              |
| 13R22.5     | 18PR       | 154        | 151  | L            | 9.75        | 9.00           | 3750         | 3450 | 830           | 830  | 1124            | 320               | 21              |
| 295/80R22.5 | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 900           | 900  | 1044            | 298               | 18.5            |
| 315/80R22.5 | 18PR       | 154        | 151  | M            | 9.00        | 9.00,9.75      | 3750         | 3450 | 830           | 830  | 1076            | 312               | 21              |
| 315/80R22.5 | 20PR       | 157        | 154  | K            | 9.00        | 9.00,9.75      | 4125         | 3750 | 900           | 900  | 1076            | 312               | 21              |



## HKD51


| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5 | 18PR       | 152        | 149  | L            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 23.5            |





## HKT10

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5     | 14PR       | 144        | 142  | M            | 8.25        | 7.50           | 2800         | 2650 | 720           | 720  | 1054            | 279               | 15.5            |
| 11R22.5     | 16PR       | 146        | 143  | M            | 8.25        | 7.50           | 3000         | 2725 | 830           | 830  | 1054            | 279               | 15.5            |
| 11R22.5     | 16PR       | 148        | 145  | M            | 8.25        | 7.50           | 3150         | 2900 | 850           | 850  | 1054            | 279               | 15.5            |
| 11R24.5     | 14PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 720           | 720  | 1104            | 279               | 15              |
| 11R24.5     | 16PR       | 149        | 146  | M            | 8.25        | 7.50,8.25      | 3250         | 3000 | 830           | 830  | 1104            | 279               | 15              |
| 12R22.5     | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 15              |
| 13R22.5     | 18PR       | 154        | 151  | L            | 9.75        | 9.00           | 3750         | 3450 | 830           | 830  | 1124            | 320               | 15              |
| 255/70R22.5 | 16PR       | 140        | 137  | M            | 7.50        | 7.50,8.25      | 2500         | 2300 | 830           | 830  | 930             | 255               | 13              |
| 275/70R22.5 | 16PR       | 148        | 145  | M            | 8.25        | 7.50,8.25      | 3150         | 2900 | 900           | 900  | 958             | 276               | 14              |
| 275/80R22.5 | 16PR       | 147        | 144  | M            | 8.25        | 7.50,8.25      | 3075         | 2800 | 830           | 830  | 1012            | 276               | 15              |
| 275/80R22.5 | 18PR       | 149        | 146  | M            | 8.25        | 7.50,8.25      | 3250         | 3000 | 900           | 900  | 1012            | 276               | 15              |
| 285/75R24.5 | 14PR       | 144        | 141  | M            | 8.25        | 8.25           | 2800         | 2575 | 760           | 760  | 1050            | 283               | 15              |
| 285/75R24.5 | 16PR       | 147        | 144  | M            | 8.25        | 8.25           | 3075         | 2800 | 830           | 830  | 1050            | 283               | 15              |
| 295/60R22.5 | 16PR       | 144        | 141  | M            | 9.00        | 8.25,9.00      | 2800         | 2575 | 830           | 830  | 926             | 292               | 15              |
| 295/60R22.5 | 18PR       | 150        | 147  | M            | 9.00        | 8.25,9.00      | 3350         | 3075 | 900           | 900  | 926             | 292               | 15              |
| 295/75R22.5 | 14PR       | 144        | 141  | M            | 9.00        | 8.25,9.00      | 2800         | 2575 | 760           | 760  | 1014            | 298               | 15              |
| 295/75R22.5 | 16PR       | 146        | 143  | M            | 9.00        | 8.25,9.00      | 3000         | 2725 | 830           | 830  | 1014            | 298               | 15              |
| 295/80R22.5 | 16PR       | 150        | 147  | M            | 9.00        | 8.25,9.00      | 3350         | 3075 | 830           | 830  | 1044            | 298               | 15              |
| 295/80R22.5 | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 900           | 900  | 1044            | 298               | 15              |
| 315/60R22.5 | 18PR       | 152        | 148  | M            | 9.75        | 9.00,9.75      | 3550         | 3150 | 900           | 900  | 950             | 313               | 15              |
| 315/70R22.5 | 18PR       | 154        | 150  | M            | 9.00        | 9.00,9.75      | 3750         | 3350 | 900           | 900  | 1014            | 312               | 15              |
| 315/80R22.5 | 18PR       | 154        | 151  | M            | 9.00        | 9.00,9.75      | 3750         | 3450 | 830           | 830  | 1076            | 312               | 15              |
| 315/80R22.5 | 20PR       | 157        | 154  | M            | 9.00        | 9.00,9.75      | 4125         | 3750 | 900           | 900  | 1076            | 312               | 15              |




## HKD52

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5 | 18PR       | 152        | 149  | L            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 23              |



## HKT10C

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5     | 14PR       | 144        | 142  | M            | 8.25        | 7.50           | 2800         | 2650 | 720           | 720  | 1054            | 279               | 10.5            |
| 11R22.5     | 16PR       | 146        | 143  | M            | 8.25        | 7.50           | 3000         | 2725 | 830           | 830  | 1054            | 279               | 10.5            |
| 295/75R22.5 | 14PR       | 144        | 141  | M            | 9.00        | 8.25,9.00      | 2800         | 2575 | 760           | 760  | 1014            | 298               | 10.5            |
| 295/75R22.5 | 16PR       | 146        | 143  | M            | 9.00        | 8.25,9.00      | 3000         | 2725 | 830           | 830  | 1014            | 298               | 10.5            |




## HKT11

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5 | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 15              |




## HKT12

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5 | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 15              |



## HKT90



| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 385/65R22.5 | 20PR       | 164        | ---  | K            | 11.75       | 12.25          | 5000         | ---- | 900           | ---  | 1072            | 389               | 16.7            |



## HKT15


| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim        | Applicable Rim                              | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|--------------------|---|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |                    |   | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5     | 18PR       | 152        | 149  | M            | 9.00               | 8.25,9.00                                   | 3550         | 3250 | 930           | 930  | 1085            | 300               | 15              |
| ST235/85R16 | 14PR       | 126        | 123  | M            | 6 <sup>1/2</sup> J | 6J,6 <sup>1/2</sup> J,7J,7 <sup>1/2</sup> J | 1700         | 1550 | 760           | 760  | 806             | 235               | 9.5             |





## HKA20

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim    | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|-------------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                   | Single       | Dual | Single        | Dual |                 |                   |                 |
| 6.50R16LT   | 12PR       | 110        | 105  | L            | 5.50F       | 5.00E,5.00F       | 1060         | 925  | 670           | 670  | 750             | 185               | 12              |
| 7.00R16LT   | 14PR       | 118        | 114  | L            | 5.50F       | 6.00G             | 1320         | 1180 | 770           | 770  | 775             | 200               | 13              |
| 7.50R16LT   | 14PR       | 122        | 118  | L            | 6.00G       | 5.50F,6.00G,6.50H | 1500         | 1320 | 770           | 770  | 805             | 215               | 12.5            |
| 8.25R16LT   | 14PR       | 126        | 122  | L            | 6.50H       | 6.00G,6.5         | 1700         | 1500 | 670           | 670  | 855             | 235               | 13              |
| 8.25R16LT   | 16PR       | 128        | 124  | L            | 6.50H       | 6.00G,6.5         | 1800         | 1600 | 770           | 770  | 855             | 235               | 13              |
| 8.25R20     | 16PR       | 139        | 137  | K            | 6.50        | 6.50T,7.0,7.00T   | 2430         | 2300 | 930           | 930  | 974             | 236               | 14              |
| 9.00R20     | 16PR       | 144        | 142  | K            | 7.00        | 7.00T,7.50        | 2800         | 2650 | 900           | 900  | 1019            | 259               | 15              |
| 10.00R20    | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00        | 3250         | 3000 | 930           | 930  | 1054            | 278               | 15              |
| 11.00R20    | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50        | 3550         | 3250 | 930           | 930  | 1085            | 293               | 16              |
| 12.00R20    | 18PR       | 154        | 151  | K            | 8.50        | 8.50V,9.00        | 3750         | 3450 | 830           | 830  | 1125            | 315               | 16.5            |
| 12.00R24    | 20PR       | 160        | 157  | K            | 8.50        | 8.50V,9.00        | 4500         | 4125 | 900           | 900  | 1226            | 315               | 16              |
| 11R22.5     | 14PR       | 144        | 142  | L            | 8.25        | 7.50,8.25         | 2800         | 2650 | 720           | 720  | 1054            | 279               | 16              |
| 11R22.5     | 16PR       | 146        | 143  | L            | 8.25        | 7.50,8.25         | 3000         | 2725 | 830           | 830  | 1054            | 279               | 16              |
| 11R24.5     | 14PR       | 146        | 143  | L            | 8.25        | 7.50,8.25         | 3000         | 2725 | 720           | 720  | 1104            | 279               | 16              |
| 11R24.5     | 16PR       | 149        | 146  | L            | 8.25        | 7.50,8.25         | 3250         | 3000 | 830           | 830  | 1104            | 279               | 16              |
| 12R22.5     | 18PR       | 152        | 149  | K            | 9.00        | 8.25,9.00         | 3550         | 3250 | 930           | 930  | 1085            | 300               | 17              |
| 295/80R22.5 | 18PR       | 152        | 149  | L            | 9.00        | 8.25,9.00         | 3550         | 3250 | 900           | 900  | 1044            | 298               | 16              |
| 315/80R22.5 | 20PR       | 157        | 154  | K            | 9.00        | 9.00,9.75         | 4125         | 3750 | 900           | 900  | 1076            | 312               | 16.5            |




## HKA20+

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11.00R20 | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50     | 3550         | 3250 | 930           | 930  | 1085            | 293               | 16              |
| 12.00R20 | 18PR       | 154        | 151  | K            | 8.50        | 8.50V,9.00     | 3750         | 3450 | 830           | 830  | 1125            | 315               | 16.5            |



## HKA10

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim    | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|-------------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                   | Single       | Dual | Single        | Dual |                 |                   |                 |
| 6.50R16LT   | 12PR       | 110        | 105  | L            | 5.50F       | 5.00E,5.00F       | 1060         | 925  | 670           | 670  | 750             | 185               | 10.5            |
| 7.00R16LT   | 14PR       | 118        | 114  | L            | 5.50F       | 6.00G             | 1320         | 1180 | 770           | 770  | 775             | 200               | 11              |
| 7.50R16LT   | 14PR       | 122        | 118  | L            | 6.00G       | 5.50F,6.00G,6.50H | 1500         | 1320 | 770           | 770  | 805             | 215               | 12.5            |
| ST235/85R16 | 14PR       | 126        | 123  | L            | 6 1/2J      | 6J,6 1/2J,7 1/2J  | 1700         | 1550 | 760           | 760  | 806             | 235               | 10.5            |
| 215/75R17.5 | 16PR       | 128        | 126  | M            | 6.00        | 6.75              | 1800         | 1700 | 750           | 750  | 767             | 211               | 13              |
| 215/75R17.5 | 16PR       | 127        | 124  | M            | 6.00        | 6.75              | 1750         | 1600 | 830           | 830  | 767             | 211               | 13              |
| 215/75R17.5 | 16PR       | 135        | 133  | J            | 6.00        | 6.75              | 2180         | 2060 | 850           | 850  | 767             | 211               | 13              |
| 235/75R17.5 | 16PR       | 132        | 129  | M            | 6.75        | 6.75,7.50         | 2000         | 1850 | 830           | 830  | 797             | 233               | 13              |
| 235/75R17.5 | 16PR       | 143        | 141  | J            | 6.75        | 6.75,7.50         | 2725         | 2575 | 850           | 850  | 797             | 233               | 13              |
| 225/70R19.5 | 14PR       | 128        | 126  | L            | 6.75        | 6.75,6.00         | 1800         | 1700 | 760           | 760  | 811             | 226               | 14              |
| 245/70R19.5 | 14PR       | 133        | 131  | L            | 7.50        | 6.75,7.50         | 2060         | 1950 | 760           | 760  | 839             | 248               | 14              |
| 265/70R19.5 | 14PR       | 137        | 134  | L            | 7.50        | 7.50,8.25         | 2300         | 2120 | 760           | 760  | 867             | 262               | 14              |
| 265/70R19.5 | 16PR       | 140        | 138  | L            | 7.50        | 7.50,8.25         | 2500         | 2360 | 775           | 775  | 867             | 262               | 14              |
| 265/70R19.5 | 18PR       | 143        | 141  | J            | 7.50        | 7.50,8.25         | 2725         | 2575 | 850           | 850  | 867             | 262               | 14              |
| 285/70R19.5 | 16PR       | 146        | 144  | L            | 8.25        | 7.50,8.25,9.00    | 3000         | 2800 | 900           | 900  | 895             | 283               | 14              |
| 8R22.5      | 14PR       | 130        | 128  | L            | 6.00        | 5.25,6.00,6.75    | 1900         | 1800 | 830           | 830  | 935             | 203               | 13              |
| 9R22.5      | 14PR       | 136        | 134  | L            | 6.75        | 6.00,6.75,7.50    | 2240         | 2120 | 830           | 830  | 974             | 229               | 14              |
| 10R22.5     | 16PR       | 144        | 142  | L            | 7.50        | 6.75,7.50         | 2800         | 2650 | 900           | 900  | 1020            | 254               | 14              |



## HKA10+

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 215/75R17.5 | 16PR       | 127        | 124  | M            | 6.00        | 6.75           | 1750         | 1600 | 830           | 830  | 767             | 211               | 13              |
| 215/75R17.5 | 16PR       | 135        | 133  | J            | 6.00        | 6.75           | 2180         | 2060 | 850           | 850  | 767             | 211               | 13              |





## HKA22

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12.00R24 | 20PR       | 160        | 157  | K            | 8.50        | 8.50V,9.0      | 4500         | 4125 | 900           | 900  | 1226            | 315               | 15              |



## HKA92

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 385/65R22.5 | 20PR       | 164        | ---  | K            | 11.75       | 11.75,12.25    | 5000         | ---- | 900           | ---  | 1072            | 389               | 18              |
| 425/65R22.5 | 20PR       | 165        | ---  | K            | 13.00       | 11.75,13.00    | 5100         | ---- | 825           | ---  | 1124            | 422               | 18              |
| 445/65R22.5 | 20PR       | 169        | ---  | K            | 13.00       | 13.00,14.00    | 5800         | ---- | 900           | ---  | 1150            | 444               | 18              |



## HKA91

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 385/55R22.5 | 20PR       | 160        | ---  | K            | 12.25       | 11.75,12.25    | 4500         | ---- | 900           | ---  | 996             | 386               | 15              |
| 385/65R22.5 | 20PR       | 160        | ---  | L            | 11.75       | 12.25          | 4500         | ---- | 900           | ---  | 1072            | 389               | 16              |
| 425/65R22.5 | 20PR       | 164        | ---  | K            | 12.25       | 11.75,13.00    | 5000         | ---- | 830           | ---  | 1124            | 422               | 16              |
| 425/65R22.5 | 20PR       | 165        | ---  | K            | 13.00       | 11.75,13.00    | 5150         | ---- | 825           | ---  | 1124            | 422               | 16              |
| 445/65R22.5 | 20PR       | 169        | ---  | K            | 13.00       | 13.00,14.00    | 5800         | ---- | 900           | ---  | 1150            | 444               | 15              |



## HKA23

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5 | 18PR       | 152        | 149  | K            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 17              |





# HKA21

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim  | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|-----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                 | Single       | Dual | Single        | Dual |                 |                   |                 |
| 6.50R16LT   | 12PR       | 110        | 105  | L            | 5.50F       | 5.00E,5.00F     | 1060         | 925  | 670           | 670  | 750             | 185               | 10.5            |
| 7.00R16LT   | 14PR       | 118        | 114  | L            | 5.50F       | 6.00G           | 1320         | 1180 | 770           | 770  | 775             | 200               | 11              |
| 7.50R16LT   | 14PR       | 122        | 118  | L            | 6.00G       | 5.50F,6.50H     | 1500         | 1320 | 770           | 770  | 805             | 215               | 12.5            |
| 8.25R16LT   | 16PR       | 128        | 124  | L            | 6.50H       | 6.00G,6.50      | 1800         | 1600 | 770           | 770  | 855             | 235               | 13              |
| 8.25R20     | 16PR       | 139        | 137  | K            | 6.50        | 6.50T,7.0,7.00T | 2430         | 2300 | 930           | 930  | 974             | 236               | 14              |
| 9.00R20     | 16PR       | 144        | 142  | K            | 7.00        | 7.00T,7.50      | 2800         | 2650 | 900           | 900  | 1019            | 259               | 15              |
| 10.00R20    | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00      | 3250         | 3000 | 930           | 930  | 1054            | 278               | 15              |
| 11.00R20    | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50      | 3550         | 3250 | 930           | 930  | 1085            | 293               | 16              |
| 12.00R20    | 18PR       | 154        | 151  | K            | 8.50        | 8.50V,9.00      | 3750         | 3450 | 830           | 830  | 1125            | 315               | 16.5            |
| 12.00R20    | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00      | 4000         | 3650 | 900           | 900  | 1125            | 315               | 16.5            |
| 12.00R24    | 20PR       | 160        | 157  | K            | 8.50        | 8.50V,9.00      | 4500         | 4125 | 900           | 900  | 1226            | 315               | 16.5            |
| 11R22.5     | 16PR       | 146        | 143  | L            | 8.25        | 7.50,8.25       | 3000         | 2725 | 830           | 830  | 1054            | 279               | 16              |
| 12R22.5     | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00       | 3550         | 3250 | 930           | 930  | 1085            | 300               | 16              |
| 12R22.5     | 16PR       | 150        | 147  | M            | 9.00        | 8.25,9.00       | 3350         | 3075 | 830           | 830  | 1085            | 300               | 16              |
| 13R22.5     | 18PR       | 158        | 156  | K            | 9.75        | 9.00            | 4250         | 4000 | 900           | 900  | 1124            | 320               | 17              |
| 13R22.5     | 18PR       | 154        | 151  | K            | 9.75        | 9.00            | 3750         | 3450 | 830           | 830  | 1124            | 320               | 17              |
| 315/80R22.5 | 18PR       | 154        | 151  | M            | 9.00        | 9.00,9.75       | 3750         | 3450 | 830           | 830  | 1076            | 312               | 16              |
| 315/80R22.5 | 20PR       | 157        | 154  | K            | 9.00        | 9.00,9.75       | 4125         | 3750 | 900           | 900  | 1076            | 312               | 16              |



# HKA24

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12R22.5 | 18PR       | 152        | 149  | K            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 16              |



# HKA21+

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 10.00R20 | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00     | 3250         | 3000 | 930           | 930  | 1054            | 278               | 15              |
| 11.00R20 | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50     | 3550         | 3250 | 930           | 930  | 1085            | 293               | 16              |
| 12.00R20 | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00     | 4000         | 3650 | 900           | 900  | 1125            | 315               | 16.5            |






## HKD34

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5 | 14PR       | 144        | 142  | M            | 8.25        | 7.50,8.25      | 2800         | 2650 | 720           | 720  | 1065            | 279               | 23              |
| 11R22.5 | 16PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 830           | 830  | 1065            | 279               | 23              |
| 11R24.5 | 14PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 720           | 720  | 1116            | 279               | 23              |
| 11R24.5 | 16PR       | 149        | 146  | M            | 8.25        | 7.50,8.25      | 3250         | 3000 | 830           | 830  | 1116            | 279               | 23              |




## HKD36

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 10.00R20 | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00     | 3250         | 3000 | 930           | 930  | 1054            | 278               | 18              |
| 11.00R20 | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50     | 3550         | 3250 | 930           | 930  | 1085            | 293               | 18              |
| 12.00R20 | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00     | 4000         | 3650 | 900           | 900  | 1125            | 315               | 18.5            |



## HKD35

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim   | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|------------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                  | Single       | Dual | Single        | Dual |                 |                   |                 |
| 8.25R20  | 14PR       | 136        | 134  | K            | 6.50        | 6.50T,7.00,7.00T | 2240         | 2120 | 830           | 830  | 974             | 236               | 15              |
| 8.25R20  | 16PR       | 139        | 137  | K            | 6.50        | 6.50T,7.00,7.00T | 2430         | 2300 | 930           | 930  | 974             | 236               | 15              |
| 10.00R20 | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00       | 3250         | 3000 | 930           | 930  | 1054            | 278               | 18              |
| 11.00R20 | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50       | 3550         | 3250 | 930           | 930  | 1085            | 293               | 18              |
| 12.00R20 | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00       | 4000         | 3650 | 900           | 900  | 1125            | 315               | 18.5            |



## HKD37

| Size      | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim   | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-----------|------------|------------|------|--------------|-------------|------------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|           |            | Single     | Dual |              |             |                  | Single       | Dual | Single        | Dual |                 |                   |                 |
| 7.50R16LT | 14PR       | 122        | 118  | L            | 6.00G       | 5.50F,6.50H      | 1500         | 1320 | 770           | 770  | 805             | 215               | 15              |
| 8.25R16LT | 16PR       | 128        | 124  | L            | 6.50H       | 6.00G,6.50       | 1800         | 1600 | 770           | 770  | 855             | 235               | 15              |
| 8.25R20   | 14PR       | 136        | 134  | K            | 6.50        | 6.50T,7.00,7.00T | 2240         | 2120 | 830           | 830  | 974             | 236               | 15              |
| 8.25R20   | 16PR       | 139        | 137  | K            | 6.50        | 6.50T,7.00,7.00T | 2430         | 2300 | 930           | 930  | 974             | 236               | 15              |
| 9.00R20   | 16PR       | 144        | 142  | K            | 7.00        | 7.00T,7.50       | 2800         | 2650 | 900           | 900  | 1019            | 259               | 16              |
| 10.00R20  | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00       | 3250         | 3000 | 930           | 930  | 1054            | 278               | 17              |
| 11.00R20  | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50       | 3550         | 3250 | 930           | 930  | 1085            | 293               | 18.5            |
| 12.00R20  | 18PR       | 154        | 151  | K            | 8.50        | 8.50V,9.00       | 3750         | 3450 | 830           | 830  | 1125            | 315               | 19              |
| 12.00R20  | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00       | 4000         | 3650 | 900           | 900  | 1125            | 315               | 19              |





## HKD37+

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11.00R20 | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50     | 3550         | 3250 | 930           | 930  | 1085            | 293               | 18.5            |
| 12.00R20 | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00     | 4000         | 3650 | 900           | 900  | 1125            | 315               | 19              |



## HKD38

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 10.00R20 | 18PR       | 149        | 146  | K            | 7.50        | 7.50V,8.00     | 3250         | 3000 | 930           | 930  | 1054            | 278               | 18.5            |
| 11.00R20 | 18PR       | 152        | 149  | K            | 8.00        | 8.00V,8.50     | 3550         | 3250 | 930           | 930  | 1085            | 293               | 20              |
| 12.00R20 | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00     | 4000         | 3650 | 900           | 900  | 1125            | 315               | 20.5            |



## HKD53

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5     | 16PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 830           | 830  | 1065            | 279               | 18              |
| 12R22.5     | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1096            | 300               | 19              |
| 13R22.5     | 18PR       | 154        | 151  | L            | 9.75        | 9.00           | 3750         | 3450 | 830           | 830  | 1136            | 320               | 20              |
| 225/70R19.5 | 14PR       | 128        | 126  | M            | 6.75        | 6.00,6.75      | 1800         | 1700 | 760           | 760  | 817             | 226               | 15              |
| 245/70R19.5 | 16PR       | 136        | 134  | L            | 7.50        | 6.75,7.50      | 2240         | 2120 | 825           | 825  | 839             | 248               | 15              |
| 265/70R19.5 | 16PR       | 140        | 138  | M            | 7.50        | 6.75,7.50,8.25 | 2500         | 2360 | 775           | 775  | 867             | 262               | 15.5            |
| 265/70R19.5 | 18PR       | 143        | 141  | J            | 7.50        | 6.75,7.50,8.25 | 2725         | 2575 | 850           | 850  | 867             | 262               | 15.5            |
| 275/70R22.5 | 16PR       | 148        | 145  | M            | 8.25        | 7.50,8.25      | 3150         | 2900 | 900           | 900  | 958             | 276               | 18.5            |
| 285/70R19.5 | 16PR       | 146        | 144  | M            | 8.25        | 7.50,8.25,9.00 | 3000         | 2800 | 900           | 900  | 895             | 283               | 16.5            |
| 285/70R19.5 | 18PR       | 150        | 148  | J            | 8.25        | 7.50,8.25,9.00 | 3350         | 3150 | 900           | 900  | 895             | 283               | 16.5            |
| 295/60R22.5 | 16PR       | 144        | 141  | L            | 9.00        | 8.25,9.00      | 2800         | 2575 | 830           | 830  | 926             | 292               | 20              |
| 295/60R22.5 | 18PR       | 150        | 147  | L            | 9.00        | 8.25,9.00      | 3350         | 3075 | 900           | 900  | 926             | 292               | 20              |
| 295/80R22.5 | 16PR       | 150        | 147  | M            | 9.00        | 8.25,9.00      | 3350         | 3075 | 830           | 830  | 1050            | 298               | 19              |
| 295/80R22.5 | 18PR       | 152        | 149  | M            | 9.00        | 8.25,9.00      | 3550         | 3250 | 900           | 900  | 1050            | 298               | 19              |
| 315/60R22.5 | 18PR       | 152        | 148  | M            | 9.75        | 9.00,9.75      | 3550         | 3150 | 900           | 900  | 950             | 313               | 18              |
| 315/70R22.5 | 18PR       | 154        | 150  | M            | 9.00        | 9.00,9.75      | 3750         | 3350 | 900           | 900  | 1014            | 312               | 19              |
| 315/80R22.5 | 20PR       | 157        | 154  | M            | 9.00        | 9.00,9.75      | 4125         | 3750 | 900           | 900  | 1082            | 312               | 19              |





## HKD32

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 13R22.5     | 18PR       | 154        | 151  | L            | 9.75        | 9.00           | 3750         | 3450 | 830           | 830  | 1136            | 320               | 21              |
| 13R22.5     | 18PR       | 154        | 151  | K            | 9.75        | 9.00           | 3750         | 3450 | 830           | 830  | 1136            | 320               | 21              |
| 315/80R22.5 | 18PR       | 156        | 150  | K            | 9.00        | 9.00,9.75      | 4000         | 3350 | 850           | 850  | 1082            | 312               | 21              |
| 315/80R22.5 | 20PR       | 157        | 154  | L            | 9.00        | 9.00,9.75      | 4125         | 3750 | 900           | 900  | 1082            | 312               | 21              |



## HKD33

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5     | 16PR       | 148        | 145  | L            | 8.25        | 7.50,8.25      | 3150         | 2900 | 850           | 850  | 1054            | 279               | 21              |
| 12R22.5     | 18PR       | 152        | 149  | L            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1085            | 300               | 21              |
| 295/80R22.5 | 18PR       | 152        | 149  | L            | 9.00        | 8.25,9.00      | 3550         | 3250 | 900           | 900  | 1044            | 298               | 21              |



## HKD39

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12.00R24 | 20PR       | 160        | 157  | K            | 8.50        | 8.50V,9.00     | 4500         | 4125 | 900           | 900  | 1226            | 315               | 19              |



## HKM70

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5 | 16PR       | 148        | 145  | G            | 8.25        | 7.50,8.25      | 3150         | 2900 | 850           | 850  | 1065            | 279               | 23              |
| 12R22.5 | 18PR       | 152        | 149  | G            | 9.00        | 8.25,9.00      | 3550         | 3250 | 930           | 930  | 1096            | 300               | 23              |



## HKM75

| Size      | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim   | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-----------|------------|------------|------|--------------|-------------|------------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|           |            | Single     | Dual |              |             |                  | Single       | Dual | Single        | Dual |                 |                   |                 |
| 8.25R16LT | 16PR       | 128        | 124  | F            | 6.50H       | 6.00G,6.50       | 1800         | 1600 | 770           | 770  | 865             | 235               | 17              |
| 8.25R20   | 16PR       | 139        | 137  | F            | 6.50        | 6.50T,7.00,7.00T | 2430         | 2300 | 930           | 930  | 986             | 236               | 19              |
| 9.00R20   | 16PR       | 144        | 142  | F            | 7.00        | 7.00T,7.50       | 2800         | 2650 | 900           | 900  | 1030            | 259               | 20              |
| 10.00R20  | 18PR       | 149        | 146  | F            | 7.50        | 7.50V,8.00       | 3250         | 3000 | 930           | 930  | 1065            | 278               | 22              |
| 11.00R20  | 18PR       | 152        | 149  | D            | 8.00        | 8.00V,8.50       | 3550         | 3250 | 930           | 930  | 1096            | 293               | 22              |
| 12.00R20  | 20PR       | 156        | 153  | D            | 8.50        | 8.50V,9.00       | 4000         | 3650 | 900           | 900  | 1136            | 315               | 22.5            |



## HKM71


| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11.00R20 | 18PR       | 152        | 149  | D            | 8.00        | 8.00V,8.50     | 3550         | 3250 | 930           | 930  | 1096            | 293               | 24              |
| 12.00R20 | 20PR       | 156        | 153  | D            | 8.50        | 8.50V,9.00     | 4000         | 3650 | 900           | 900  | 1136            | 315               | 24.5            |





## HKM76

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim   | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|------------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                  | Single       | Dual | Single        | Dual |                 |                   |                 |
| 7.50R16LT   | 14PR       | 122        | 118  | F            | 6.00G       | 5.50F,6.50H      | 1500         | 1320 | 770           | 770  | 815             | 215               | 16.5            |
| 8.25R16LT   | 16PR       | 128        | 124  | F            | 6.50H       | 6.00G,6.50       | 1800         | 1600 | 770           | 770  | 865             | 235               | 17.5            |
| 8.25R20     | 14PR       | 136        | 134  | F            | 6.50        | 6.50T,7.00,7.00T | 2240         | 2120 | 830           | 830  | 986             | 236               | 17.5            |
| 8.25R20     | 16PR       | 139        | 137  | F            | 6.50        | 6.50T,7.00,7.00T | 2430         | 2300 | 930           | 930  | 986             | 236               | 17.5            |
| 295/80R22.5 | 18PR       | 152        | 149  | K            | 9.00        | 8.25,9.00        | 3550         | 3250 | 900           | 900  | 1050            | 298               | 19              |



## HKM77

| Size     | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|----------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|          |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 12.00R20 | 20PR       | 156        | 153  | K            | 8.50        | 8.50V,9.00     | 4000         | 3650 | 900           | 900  | 1136            | 315               | 22              |







# HKW81

| Size        | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|-------------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|             |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 315/80R22.5 | 18PR       | 154        | 151  | M            | 9.00        | 9.00,9.75      | 3750         | 3450 | 830           | 830  | 1082            | 312               | 24              |



# HKW82

| Size    | Ply Rating | Load Index |      | Speed Symbol | Standed Rim | Applicable Rim | Max Load(kg) |      | Pressure(kpa) |      | Overall DIM(mm) | Section Width(mm) | Tread Depth(mm) |
|---------|------------|------------|------|--------------|-------------|----------------|--------------|------|---------------|------|-----------------|-------------------|-----------------|
|         |            | Single     | Dual |              |             |                | Single       | Dual | Single        | Dual |                 |                   |                 |
| 11R22.5 | 16PR       | 146        | 143  | M            | 8.25        | 7.50,8.25      | 3000         | 2725 | 830           | 830  | 1065            | 279               | 21              |

